



# Valspar® Pro-Hide® High Holdout Primer

---

## Series 91117

### GENERAL DESCRIPTION

Valspar® Pro-Hide® Interior High Holdout Latex Primer is a primer and finisher formula that helps to improve the finish of all topcoats. Offering excellent hide, Valspar® Pro-Hide® High Holdout Primer helps to promote a smooth, even finish to further minimize surface imperfections when applied over surfaces of various porosity.

#### **Product Features:**

- Primes & finishes
- High-quality eggshell finish
- Smooth, even finish
- Excellent hide
- Minimizes surface imperfections

### WHERE TO USE

Properly prepared interior drywall, masonry, plaster, wood, and previously painted surfaces.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Gallon – 4 per carton  
5 Gallon

### COMPOSITION

#### **Base and Fill Levels**

(oz./gal.)

White 128

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply when air, surface and product temperatures are above 50°F. No reduction necessary. If applying by spray back-rolling is recommended for drywall, plaster and masonry.

#### **Airless Spray:**

**Pressure:** 2000 PSI

**Tip:** 0.017–0.021"

**Brush:** Premium-quality

**Roller:** Premium-quality roller

### CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### PRODUCT SPECIFICATIONS

**Vehicle:** Vinyl Acrylic

**Finish:** 25-35 units @ 85°

**Flash Point:** N/A

**Volume Solids:** 26 ± 2%

**Weight Solids:** 42± 2%

**Weight/Gallon:** 10.7 lb/gal

**VOC (less exempt solvents):** < 100 g/L as per 40 CFR 59.406

**Spread Rate:** up to 400 sq. ft. per gallon, @ 4 mils wet; 1.0 mils dry

**Drying Time (@ 77°F, 50% R.H.):**

**To Touch:** 1 hour

**To Recoat:** 4 hours

**Note:** Drying times are temperature, humidity and film thickness dependent.



# Valspar® Pro-Hide® High Holdout Primer

---

## Series 91117

### **SURFACE PREPARATION**

Surface should be clean, dry and dull. Remove all contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand existing, peeling or cracking paint to a sound surface. Sand glossy surfaces. Drywall: Fill cracks and holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust. Masonry, Concrete, Block: All new surfaces must be cured according to the supplier's recommendations — usually about 30 days and should have a pH between 5 and 9 and moisture content of 15% or less. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. Plaster: Bare plaster must be hard and cured. Treat textured, soft, porous or powdery plaster with a solution of 1-pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry. Wood, Pre-Primed Fiberboard, Hardboard, Plywood: Sand any exposed wood to a fresh, smooth surface. Patch all holes and imperfections with a wood filler or putty, and sand smooth. Remove all sanding dust.

### **LIMITED WARRANTY**

This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. [Valsparpaint.com/1-877-VALSPAR](http://Valsparpaint.com/1-877-VALSPAR).

### **LEAD WARNING**

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **CAUTIONS**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 9/21/22  
Version: 91117